

**EFPR800KN**

DESIGNED  
TO PROTECT



**Air**

CLEAR KN LENS



**Features**

- ▲ Certified medium impact rated protection to AS/NZS 1337.1:2010
- ▲ KN Rated lens offers the ultimate in anti-scratch (K) permanent anti-fog (N) performance.  
Perfect in applications where extreme scratching and fogging occurs
- ▲ Base 9.5 curve provides excellent optical clarity and an extended wrap for increased side protection
- ▲ World's lightest safety spectacle at only 16 grams
- ▲ UV400 Polycarbonate lenses offer the wearer the best protection against UVA and UVB damaging rays
- ▲ Ultra thin lenses provide outstanding optical clarity
- ▲ Made from 100% durable and resilient polycarbonate
- ▲ Connection point for spec cord or lanyard
- ▲ Universal nose bridge that suits most faces

**Standards & Certification**

Force360 recognise that without product certification by a Notified Body all product performance testing, and adherence to standards claims cannot be independently verified.

If they are not as claimed, serious safety implications for the wearer, and legal implications for the supplier and even the employer may arise.

Force360 source their entire range of FPR eye protection from a single manufacturing partner to ensure consistency and reliability of product, but most importantly Force360 have taken the further step of engaging a globally recognised Notified Body to audit and certify both the manufacturing process and the products.

All of Force360's eye protection is certified to the latest AS/NZS eye protection standards.



**Specifications**

<b>Part No.</b>	EFPR800KN
<b>Lens Colour</b>	Clear KN Lens
<b>VLT Rating</b>	92%
<b>Lens Shade Category</b>	0

**Packaging**

1 12 144

**Alternative Lens Options**

- EFPR800**  
Clear
- EFPR800AR**  
Clear Anti-Reflective
- EFPR801**  
Smoke
- EFPR802**  
Light Brown
- EFPR803**  
Silver Mirror

## EFPR800

### Key Technologies



#### Medium Impact

Certified medium impact rated protection to AS/NZS 1337.1:2010.



#### KN Rated Lens

KN coated safety eyewear offers the ultimate in anti scratch (K) and permanent anti fog (N) performance. Under European Standards EN166 safety eyewear with a KN coating must pass strict performance levels. KN coated lenses should be used in applications where extreme scratching and fogging occurs.



#### UV400

UV400 Polycarbonate lenses offer the wearer the best protection against UVA and UVB damaging rays. 100% protection is the standard across the entire Force360 FPR eyewear range.

### Radiation Guide

<b>UVA/UVB 280-380nm</b>	UV light rays from the sun are invisible to the eye yet can cause serious damage including corneal blistering, cataracts, premature aging, conjunctivitis and partial blindness
<b>Visible Light 380-780nm</b>	Intense visual bright light can cause retina damage and create visual perception issues
<b>Blue Light 380-500nm</b>	Blue light rays from the sun or artificial lighting like neons, cause eye strain and fatigue. Colours and definition can be adversely affected. In extreme cases blindness can occur
<b>Infra Red Light 780-1400nm</b>	Infra Red rays from the sun or mechanically heat generating applications like gas welding can cause eye dryness and corneal damage, macular degeneration and blindness

### Range Specifications

Force360 Code	Product Name	Lens Type	Temple Colours	Coating	OC Category	Lens Markings	UV Light Absorption: 280-380NM	Visible Light Transmission: 380-780NM	Blue Light Absorption: 380-500NM	Infrared Light Absorption: 780NM-1400NM
EFPR800	Air	clear	clear	AF/HC	0	I00	100%	89%	12%	9.76%
EFPR800AR	Air	clear	lime green	AR	0	I00	100%	89%	12%	9.76%
<b>EFPR800KN</b>	<b>Air</b>	<b>clear</b>	<b>blue</b>	<b>KN</b>	<b>0</b>	<b>I00</b>	<b>100%</b>	<b>92%</b>	<b>12%</b>	<b>9.76%</b>
EFPR801	Air	smoke	smoke	AF/HC	2	I2	100%	23%	77%	46.84%
EFPR802	Air	light brown	light brown	AF/HC	1	I1	100%	59%	52%	20.27%
EFPR803	Air	silver mirror	silver mirror	HC	2	I2	100%	27%	77%	43.21%

### Eyewear Care

Force360 recommends eyewear is cleaned using Force360's exclusive FogOff non alcohol spec wipe. Part number EFPR950.

### Weight



16g	17-20g	21-25g	26-30g	31-35g	36g+
-----	--------	--------	--------	--------	------